

MM-3000

With the sleek elegant design and the plastic and aluminum combined housing, the MM-3000 is a state of the art POS monitor for all your POS needs. Whether operating in humid hot or dusty areas, the MM-3000 can function competently under any environment circumstances. With various options to extend the functionality of unique POS monitors, the MM-3000 can cater for all your business needs.



- 5-wire resistive touch screen and MCR
- Robust die-cast aluminum stand with considerate mechanical design for optional customer VFD or LCD pole display
- The sleek elegant design with integrated plastic housing providing an economic choice for POS monitors

Specifications

Model	MM-3015
LCD Display Size	15" TFT LCD
Resolution	1024 X 768 (XGA)
Max. Color	16.7M
LCD Brightness	250 / 350 cd/m ²
Contrast Ratio	500 : 1
Touch Screen	5 / 4 wire Resistive
I/O Connectivity	
Serial Port	1 x COM (D-Sub 9-pin) for Touchscreen
PS/2	1 x Keyboard for Magnetic Stripe Card Reader
Video Port	1 x VGA (D-Sub 15-pin)
DC-in Port	DC +12V/4A Input
Construction	Injection-Molded, Plastic+Aluminum Housing, spill resistance
Housing Color	Charcoal+Silver / Charcoal+Red
Dimensions (W x H x D)	360 x 330 x 200 mm
Weight	6.5 Kgs
EMI/Safety	CE, FCC
Operating Temperature	0°C ~ 35°C
Optional Peripherals	
Magnetic Stripe Card Reader	Integrated single/dual/triple Track MCR
Customer Pole Display	Integrated VFD/LCD Customer Pole Display

