



POS TS-201

Application Benefits :

Slim & Stylish Look

Improved reliability

Service & Upgrade with ease

Fits Various retail & hospitality environments



Black



White



TS-201

**15" Ultra Wide LCD
and Back light**

True-Flat PCAP Touch

**High speed Intel
Processor**

**Fanless(Celeron) and Silent
heat solution**

**Easy Swap HDD
Lack type**

**Structure for easy
maintenance**

**MSR/iButton for
Identification**

**Dual Display and
Customer Display**

Specification

Processor	Intel® Celeron® J6412	Intel Core 11th i3/i5/i7
Memory	DDR4/DDR3 Standard 4GB (up to 16GB) Socket 1 x SODIMM	DDR4 Standard 4GB (up to 16GB) Socket 1 x SODIMM
HDD	2.5" SSD 128GB (up to 1TB) / *Option M.2	
LCD	15.1" TFT LCD(Wide view) 1024*768 LED Backlight, 300 ~350 cd/m ² (typ.)	
Touch	10 Point Capacitive Touch, USB interface Full-window type	
OS	Windows 10 IoT / Linux	
Rear IO	1x DC-12V 4-pin Power Input Connector 1x VGA Port with Power out(12V) 1x Ethernet Port (Gigabit RJ45) 2x USB (3.0) Serial port - COM1~2 (D-SUB 9Pin 5V/12V by BIOS) COM3~4 (RJ45 with flow control, 5V/12V by BIOS) COM5 (RJ45 only RX/TX with 5V, Reserved for MSR with USB) 1x Audio Jack (Line-out)	
Back IO	4x USB (2.0) RJ11 For CR Port (Virtual Com port)	
Sound	1 x 1W (Mono), *option 2 x 1W (Stereo)	
Option	2nd Display : 9.7" TFT LCD (1024 x 768), RGB Interface, Optional Touchscreen VFD Customer Display, 20 Columns x 2 Lines Identification Reader (3 Track-HID & i-Button) by USB, Wall Mount Bracket	
Dimension	364mm(W) * 340mm(H) * 210mm(D)	
Certification	FCC, CE, KC	
Color	White, Black	
Power	60W Adaptor Input 100~240V/50~60Hz, Output DC 12V/5A	



BST KOREA Co., Ltd.

Starwith Bdg, Unit 1011,
Heungan-daero 427 beon-gil 38
Dongan-gu, Anyang-si
Gyeonggi-do, Rep. of Korea

Web www.bstkr.com

Mail sales@bstkr.com

Tel +82-1577-8764

Accessory (Option)



Dual Monitor



Customer Display



Identification Reader



Wall Mount
Bracket

Port

